


DESCRIPTION

60 Hz



*Referential image



60 Hz

HH

Power , [kW / HP]	26 / 35
Voltage, V	380 / 440 / 460
Nominal current, A	50,1 / 43,3 / 41,4
Weight, kg	195
Max. height, mm	1234
Max. width, mm	461
Discharge, in	4"
Strainer opening Ø, mm	12

Electric submersible drainage pump, available in various aluminum and stainless-steel alloys. For applications in mines, power plants and other industries that handle abrasive solids and water.

Models:

HH: Max. pressure.

Classification

Submersible electric pump

Electric motor

Three-phase squirrel cage motor
Speed: 3550 RPM
Insulation class: H
Start: Direct
Max. number of starts per hour: 12

Motor protection

Termocontactos en el bobinado
Protección: IP 68

Cable

4G10 + 2x1.5mm², 20m (*).

This pump must be connected to an external electrical cabinet with adequate protections.

Mechanical seals

Double mechanical seal in oil chamber and water.
Rotary seal material: silicon carbide.
Stationary seal material: silicon carbide.
Elastomers: Viton.

Bearings

Lower: Angular contact bearing C3
Upper: Deep groove ball bearing C3

Discharge connection

4" HH

Limitations

Maximum submersion: 20 m.
Maximum liquid temperature: 40 °C (104°F).
Liquid pH range: 5 – 8.

Available materials

Cover: Aluminum.
Cylinder: Carbon steel.
Strainer: Carbon steel.
Impeller: High chrome steel / Stainless steel.
Diffusers: Aluminum + PU / High chrome steel.
Shaft: AISI 431 Stainless steel.
Screws / Nuts: Stainless steel.

**Specifications may be modified without prior*