

Bronco 99MD

Electric submersible slurry pump

50 Hz

*Referential image
Also available in a stainless steel version.



Electric submersible slurry pump, available in various cast iron and stainless-steel alloys. For applications in mines and industries that handle abrasive solids and slurries.

50 Hz	MD
Power, [kW / HP]	60 / 80
Voltage, V	380 / 400 / 500
Nominal current, A	150,9 / 143,4 / 114,7
Weight, kg	1215
Max. height, mm	1850
Max. width, mm	990
Discharge, in.	8"
Strainer opening Ø, mm	45

Model:

MD: Medium Duddy

Classification

Submersible slurry pump

Electric motor

Three-phase squirrel cage motor
Speed: 1450 RPM
Insulation class: H
Start: Star-Delta, Soft Starter
Max. number of starts per hour: 12

Motor protection

Thermo-contacts in the winding
Protection: IP 68

Cable

2 cables 4G35 + 2x1.5mm², 20m. (*)

Mechanical seals

Double mechanical seal in oil chamber.
Rotary seal material: silicon carbide.
Stationary seal material: silicon carbide.
Elastomers: Viton.

Discharge connection

8" (*)


Limitations

Maximum submersion: 20 m.
Maximum liquid temperature: 40 °C (104 °F)
Rango de pH líquido: 6 – 11.

Available materials

Cover: Cast iron.
Strainer: Carbon steel.
Impeller: High chrome steel / Stainless steel.
Agitator: High chrome steel.
Wear plate: High chrome steel.
Cover suction: Cast iron.
Casing / volute: Cast iron.
Shaft: AISI 431 Stainless steel.
Screws / Nuts: Stainless steel.

This pump must be connected to an external electrical cabinet with adequate protections.



*Specifications may be modified without prior notice.